

WORKSHOP 390 SWF



3 YEAR
WARRANTY

Combine immense power and smooth arc characteristics even in the toughest conditions. The WORKSHOP 390 SWF is designed for medium and heavy fabrication.

Key Features

- **Transformer Power Source**
- **Separate Wire Feeder Unit**
- **Built in Europe**

Package Contents

- WORKSHOP 390 SWF Welder
- KT50 SWF Unit
- 10m Interconnecting Cables
- 4m SB36 MIG Torch
- 10m 500 Amp Earth Clamp & Lead
- Twin Gauge Argon Regulator
- 2m Gas Hose Complete with Fittings
- 2 x 0.9-1.2 V Groove Roller
- Operating Manual

Specifications

SKU	KUM390SWF
Primary Input Voltage	415V Three-Phase
Supply Plug	Unplugged (32A Recommended)
Open Circuit Voltage - OCV (V)	18-45
Protection Class	IP21
Insulation Class	F
Minimum Generator (kVA)	19
Standard	AS 60974.1
MIG Cut Duty Cycle @ 40°C	40% @ 375A, 70% @ 355A, 100% @ 300A
Driver Rollers	2 x 40/32 (See page 213 for the full range)
Dimensions (mm)	980x660x460
Weight (kg)	161
Package Dimensions (cm)	103x71x51
Package Weight (kg)	146

